Serenitie

Exposed Thermostatic Shower Valve



Product features:

- Metal construction throughout
- Custom designed for lower range pressures
- Thermostatic valve for safety & comfort
- Freshly designed contemporary blend
- Supplied with adjustable centre inlets

Packaged properties:


Box length (mm): 380 **Box depth(mm):** 75

Box width(mm): 175 **Boxed weight (Kg):** 2.5

Includes pop up waste?: No


Additional comments:

Product dimensions:



- **Product mounted where:** Wall
- **Recommended hole size:**
- **Overall Height / projection:** 112 mm
- **Exit reach:** 66 mm
- **Exit height:**
- **Base size:** 150 ± 20 mm
- **Inlet centre distance(s):**
- **Min. fitting depth required:** 60 mm
- **Max. surface depth:**

Product flow characteristics:



- **Min / Max water pressure (bar):** 0.20* / 5.00
- **Part G max. mixed flow rate at 3 bar (l/m):** 33.7
- **Inlet connection type / length:** Eccentric / 50 mm
- **Inlet (plumbing connection) / outlet size:** 1/2" M /
- **Product flow characteristics:**
  Non return valve(s) supplied or position: h&c inlet
- **Aerator type:**
- **Control valve type:** Thermostatic ()
- **Includes output diverter?:** No
- **Inlet meshed particle filters included:** 0.60 mm
- **Shower hose type / length:**

Warranty Summary (full details available on request):

- Materials and workmanship defects warranted for 5 years
- Valves and working parts warranted for 5 years
- Surface warranty defects warranted for 1 year
- O-rings, hoses & gaskets warranted for 1 year

Care instructions:

- Clean the mixers and showers regularly as required, using soap, do not use any other cleaners.
- Regular cleaning will prevent the build up of lime scale and dirt
- After cleaning rinse thoroughly with clean water to remove any cleaner residue
- Residues of liquid soaps, shampoos and shower foams can also cause damage, so rinse with clean water after using, avoid contact with any abrasives