

Zeal

Concealed Thermostatic Shower Valve (2 Exit)





Product features:

- · Metal & ABS construction
- Thermostatic valve for safety & comfort
- 2 exit alternate control for output to 2 x shower or 1 x shower
 4 x bath
- · Minimalist planate design form
- 5 year limited warranty

Packaged properties:

Box length (mm): 250

Box depth(mm): 150

Box width(mm): 160


Boxed weight (Kg): 3.6

Includes pop up waste?: No

Additional comments:

Includes 2.5mm allen key, optional removable mesh filters and flow limiters (7 l/min)

Product dimensions:



• Product mounted where: Wall


• Recommended hole size: 200 x 170 mm

Overall Height / projection:
 Exit reach:
 Exit height:
 Base size:
 52 mm
 N/A mm
 155 x 234 mm

• Inlet centre distance(s): N/A mm

• Min. fitting depth required: 50-65 mm • Max. surface depth: N/A mm

Product flow characteristics:



• Min / Max water pressure (bar): 0.30* / 5.00

• Part G max. mixed flow rate at 3 bar (I/m): 30

• Inlet connection type / length: Fixed / N/A mm

• Inlet (plumbing connection) / outlet size: 1/2" M / 1/2" M

• Product flow characteristics: N/A

Non return valve(s) supplied or position: h&c inlet

Aerator type: N/A

• Control valve type: Thermostatic (new plastic type)

• Includes output diverter?: Yes

• Inlet meshed particle filters included: 0.6 (3/4" gasket)

• Shower hose type / length: N/A / N/A

Warranty Summary (full details available on request):

- Materials and workmanship defects warranted for 5 years
- Valves and working parts warranted for 5 years
- Surface warranty defects warranted for 1 year
 O-rings, hoses & gaskets warranted for 1 year

Care instructions:

- Clean the mixers and showers regularly as required, using soap, do not use any other cleaners.
- Regular cleaning will prevent the build up of lime scale and dirt
- After cleaning rinse thoroughly with clean water to remove any cleaner residue
- Residues of liquid soaps, shampoos and shower foams can also cause damage, so rinse with clean water after using, avoid contact with any abrasives