SOFTLINE PLAN VERTICAL

Softline Series

50 Δt

(75/65/20°C)

K2



Height mm	Length mm	Sections	Stelrad UIN	Heat output Watts	Heat output Btu/h	Price excl VAT	Price incl VAT
1800	400	12	87322418	1476	5036	£288.78	£346.54
	500	15	87322518	1845	6295	£320.21	£384.25
	600	18	87322618	2214	7554	£350.45	£420.54

Δt50 is the UK's industry standard for heating outputs, which has an operating temperature of 75/65/20°C. If you have a low temperature heat source you may wish to consider Δt40 or Δt30 output (see your installer or system designer or download from www.stelrad.com).

For EN442 data, technical and installation information please visit our website: www.stelrad.com and search product downloads.


SOFTLINE PLAN VERTICAL

Softline Series

WALL MOUNTING INFORMATION


All dimensions in mm. Inches in brackets.

K2



Comes complete with Stelrad's class leading safety bracket.

MOUNTING BRACKETS



Height		H2		H3		H4	
mm	inches	mm	inches	mm	inches	mm	inches
1800	70.87	70	2.75	830	43.89	1590	63.58


CONNECTIONS

Each radiator comes with ½" inlet connections as standard.

SOFTLINE PLAN VERTICAL

Softline Series


PIPING OPTIONS



EN 442 CERTIFICATION DATA - CETIAT TESTED IN ACCORDANCE WITH BS EN 442

Type	K2
Height	1800
W/m at 75/65/20	3690
n-coefficients	1.32
Heated surface area (m^2/m)	29.90
Weight (kg/m)	105.30
Water contents (l/m)	15.90
Wall to tap centre (mm)	77
K_M	20.69

PRESSURE DROPS



① Type 21 (P+), 22 (K2)