



BELGRAVIA (E)

DEMOUNTABLE ACOUSTICAL CEILING

- ✓ Robust ceiling with long service life
- ✓ Simple, time-saving installation
- ✓ Sustainable

FEATURES








- T-grid ceiling
- Edge E design
- Recessed T-grid

SUSTAINABLE PRODUCT:

- Made of gypsum
- Safe material
- 100% recyclable
- Improved indoor climate
- Repaintable without loss of acoustics



PRODUCT VARIANTS

EDGE DESIGN				
	EDGE E, S15 Lay-in tile in recessed S15 T-grid	EDGE E, S24 Lay-in tile in recessed S24 T-grid	EDGE E, FINELINE Lay-in tile in a C-channelled T-grid	
PERFORATION DESIGN				
Also available without perforations (Regula)				
PERFORATION MEASURES	MICRO Square 3x3 mm c/c 8.33 mm	GLOBE Circles Ø 6 mm c/c 15 mm	QUADRIL Square 12x12 mm c/c 30 mm	TANGENT Obround 4x14 mm c/c 10/20 mm
PERFORATION %	10.2%	10.2%	13%	21.3%
NRC, @ 200mm, no mineral wool	0.60	0.65	0.65	0.75
NRC, @ 200mm, 50mm mineral wool	0.70	0.70	0.75	0.90
ALPHA-W, @ 200mm, no mineral wool	0.65	0.60	0.60	0.80
ALPHA-W, @ 200mm, 50 mm mineral wool	0.70	0.65	0.70	0.90
LIGHT REFLECTION	72.1%	72.8%	75.1%	70.9%
SIZES, mm	Standard	600x600x12.5 625x625x12.5 (only S24)		600x600x12.5
Other options		300-450 x 600-2400 x 12.5 450-625 x 600-1250 x 12.5		
TILE WEIGHT, kg/m ²	9.20 - 9.90			
SURFACE TREATMENT	Front: White acrylic paint, RAL 9003, gloss 5. Back: Acoustic felt backing. Available in other colours on request. Also available with hygienic Medifend surface paint on request. Medifend has antibacterial and fungistatic effect. Tested in accordance with DIN ISO 846, method B and B'.			
SYSTEM COMPONENTS	1) Gypsum ceiling tile, 2) T24/38 or T15/38 main runner, 3) Cross tees, 4) Hangers			
CERTIFICATES	1) Environmental product declaration, 2) FDES – life cycle analysis, 3) Danish Indoor Climate Labelling, 4) ISO 16000-9 Emission of VOCs, 5) UL-listed in accordance to R26164			

PRODUCT PERFORMANCE

FIRE RATING

A2-s1, d0

AIR QUALITY

Indoor value: 10 days
Particle emission: LOW
Active air purification with
Cleaneo technology

AMBIENT CONDITIONS

Can withstand:
- constant RH 70% and 25°C
- periodic RH 90% and 30°C
- ambient temperatures of up to 50°C.

LOAD-BEARING CAPACITY

Up to 3 kg pr. tile (at max. 2mm deflection)

ROBUSTNESS

Glass fibre reinforced gypsum. High pressure resistance. Highly stable ceiling ensured by tile density.