



## **Knauf Uniflott**

Knauf Uniflott is a specially formulated joint compound for use with Knauf perforated plasterboard to create a seamless finish, and it can be used as a joint and surface filler for Knauf Brio, Knauf Hugo, and Knauf Gifa Floor.

*Product-Data-Sheet*



### **Areas of Application**

Plasterboard ceilings and floor boards.

### **Compliance Standards**

EN 13963:2014

### **Key Benefits**

- Alpha Gypsum for the strongest compound
- No tape needed (Type 4B, EN 13963:2014)
- For use with Knauf perforated plasterboards and Knauf floor boards
- Quick drying (approximately 2 hours depending on temperature and humidity)

***Build on us.***

Creation Date: 17/05/2024  
Revision Reference: 002  
Revision Date: 04/03/2025

Performance Data

Reaction to Fire (R2F)	Flexural Strength	Dangerous Substances
A1	NPD	Pass

Technical Information

Colour	Weight (kg)	Approximate Coverage (kg/m² )	Material Number
White	25	0.15 (Brio), 0.1 (Solopanel/ Stratopanel)	253631

## Sustainability

### Substances of very high Concern (SVHC)

At the time of publication, under REACH UK and REACH EU regulations this product contains no SVHC. For more information please consult the Safety Data Sheet.

### Volatile Organic Compound Content (VOC)

At the time of publication, under REACH UK and REACH EU regulations this product contains no VOCs. For more information please consult the Safety Data Sheet.

## Storage and Handling

Store in a well ventilated, cool place away from damp, with bags kept sealed. To be used in temperatures above 10°C.

## Packaging

Packaged in a triple layer bag (paper, plastic, paper), on a wooden pallet.

## Shelf Life/Service Life

9 months from the date of production, which is printed on the bag.

## Disposal/Repair

Disposal should be in accordance with local authority requirements. European waste codes: 10 01 05 – calciumbased reaction wastes from flue-gas desulphurisation in solid form 17 08 02 – gypsum-based construction materials other than those mentioned in 17 08 01. Bags should be emptied thoroughly before disposal to minimise contamination.

## Health & Safety

Goggles with side shields are recommended in case of splashing, and when sanding. Gloves are also advised, and respiratory protection if dust forms. For more information please consult the safety data sheet.

## Application / Installation

Sprinkle the Uniflott in cold, clean water (maximum 2.5kg in 1.2L of water) into a clean container. Leave for 2–3 minutes before mixing with a trowel to a creamy consistency. Apply at least 2 coats. Can be used with the Knauf Uniflott Applicator gun, a reusable cartridge with spray nozzle to apply the Uniflott into joints. Working time 45 minutes, drying time 2 hours.

## Additional Documentation

[Declaration of Performance CE](#)

[Safety Data Sheet](#)

### Product Accreditations:



### Knauf UK GmbH Company Accreditations:



The information given in this publication is believed to be current and accurate as at the date of publication, but no warranty, express or implied is given. Updates will not be automatically issued © Copyright Knauf 2024

### Customer Service

UK Tel: 0800 521 050  
Eire Tel: 01 4620739  
Email: [cservice@knauf.com](mailto:cservice@knauf.com)

### Technical Service

Tel: 0800 521050 (option 2)  
Email: [technical-uk@knauf.com](mailto:technical-uk@knauf.com)  
(excluding public holidays)

### UK Address

Knauf  
Kemsley Fields Business Park  
Sittingbourne  
Kent ME9 8SR

### Ireland Address

Knauf  
87 Broomhill Road  
Tallaght  
Dublin 24  
D24 WR85

Creation Date: 17/05/2024  
Revision Reference: 002  
Revision Date: 04/03/2025