

DECLARATION OF PERFORMANCE

No. 0022_Fliseklæber_Quick_2020-07-23

1. Unique identification code of the product-type:

EN 12004 - C 2 FT S1

- 2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4): Knauf Bauprodukte Fliseklæber Quick
- 3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

ceramic tile adhesives for internal and external tile installations on walls and floors

 Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):
Knauf Bauprodukte GmbH & Co. KG, Am Bahnhof 7, D-97346 Iphofen, Tel. +499323 31-0, Fax +499323 31-277, E-Mail info@knauf-bauprodukte.de

System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V: System 3

- In case of the declaration of performance concerning a construction product covered by a harmonised standard: Säurefliesner-Vereinigung e.V. (NB-No. 1212) performed the determination of the product-type on the basis of type testing under system 3 and issued: classification report No. Z-61891304.101. Factory production control by manufacturer.
- 9. Declared performance

| Essential characteristics | Performance | Harmonised technical specification |
|--|-------------------------|------------------------------------|
| Reaction to fire | E | EN 12004:2007+A1 :2012 |
| Dangerous substances | NPD | EN 12004:2007+A1 :2012 |
| - Early tensile adhesion strength | ≥ 0,5 N/mm ² | EN 12004:2007+A1 :2012 |
| - Initial tensile adhesion strength | ≥ 1,0 N/mm ² | |
| - Tensile adhesion strength after heat ageing | ≥ 1,0 N/mm ² | EN 12004:2007+A1 :2012 |
| - Tensile adhesion strength after water immersion | ≥ 1,0 N/mm ² | |
| - Tensile adhesion strength after freeze/thaw cycles | ≥ 1,0 N/mm² | |

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies: Not relevant

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4:

Signed for and on behalf of the manufacturer by: ppa. Ulrich Köhler (General Manager)

libli

Iphofen, 2020-07-23 (place and date of issue)