



BIO-CEL XL-2
MBR Module

Submerged MBR Modules for Wastewater Treatment

HIGH EFFLUENT QUALITY

Submerged MBR modules are state-of-the-art technology and MANN+HUMMEL Water & Fluid Solutions developed BIO-CEL to meet the needs of biological wastewater treatment plants around the world.

The increasing acceptance of MBR technology worldwide not only results in growth of the MBR market but also in an increase in large-scale projects with more than 10,000 m³/d inflow to the MBR plant. In order to address these demands, MANN+HUMMEL Water & Fluid Solutions developed the BIO-CEL XL-2 module. With this module, there is only one connection point for permeate and air for the total membrane area (1,920 m²), this roughly equates to > 1,000 m³/d of wastewater to be treated.

For customers with large-scale applications, the BIO-CEL XL-2 modules could be the perfect fit.



MATERIAL DATA⁽¹⁾

Membrane area	1920 m ² (20667 ft ²)	Connection permeate	Lapped flange DN125, PN10, PVC
Recommended air scour rate	360 Nm ³ /h (212 SCFM)	Dry Weight	750 kg (1653 lb)
Length	3200 mm (10.5 ft)	Membrane	PES
Width	2750 mm (9.0 ft)	Housing	Stainless Steel
Height	2750 mm (9.0 ft)	Drainage	Polyester
Connection aeration	Lapped flange DN125, PN10, PP	Diffusor	Membrane hose: PUR / SI Support tube: PP

Note: (1) nominal values

Americas

USA: +1 805 964 8003

sales.mnus@microdyn-nadir.com

Asia

APAC: +65 6457 7533

China: +86 10 8413 9860

waterchina@mann-hummel.com

Europe

Germany: +49 611 7118 7480

Italy: +39 0721 1796201

info.wfs@mann-hummel.com

MANN+
HUMMEL

www.mann-hummel.com