

NADIR MP005 P

Microfiltration Membrane

NADIR MP005 is a polyethersulfone (PES) microfiltration membrane with a pore size of 0.05 micron. This high-flux membrane is often used to remove macromolecules and concentrate large organic solutes. MP005 membrane sheet is available in dry flat sheet rolls and is FDA compliant.

MEMBRANE CHARACTERISTICS

Membrane Chemistry	Polyethersulfone (PES)
Backing Material	Polypropylene
Nominal Pore Size (µm)	0.05
Permeability LMH/bar (GFD/psi) ^a	≥285 (≥11.6)
Thickness (µm)	210 - 250
pH Range	0.0 -14.0

a) Test conditions: Clean water, 2 bar (29 psi), 20°C (68°F), crossflow operation. Membrane specifications may change without notice as design revisions occur.

IMPORTANT INFORMATION

Standard Sizes: NADIR flat sheet membrane is available in an A4 sample size of 200 mm x 300 mm (7.87 in x 11.81 in) and in a nominal roll size of 150 m x 1016 mm (492 ft x 40.0 in). Custom lengths may be available on request

Initial Flush: MANN+HUMMEL Water & Membrane Solutions recommends flushing membrane for 30 minutes and discarding permeate during the flush prior to operation.

Storage: Membrane shipped dry should be stored away from direct sunlight in a cool, dry place. Please see Membrane Storage Guide – Flat Sheet Membrane (TSG-O-011).

Contact

Americas

USA: +1 805 964 8003
sales.mnus@microdyn-nadir.com

Asia

APAC: +65 6457 7533
info.wfs@mann-hummel.com
China: +86 10 8413 9860
waterchina@mann-hummel.com

Europe

Germany: +49 611 7118 7480
Italy: +39 0721 1796201
info.wfs@mann-hummel.com

Leadership in Filtration

Rev. 2501

MANN+
HUMMEL