

Product Information

XTEND 5W40



Description

XTEND 5W40 is a premium motor oil formulated with fully synthetic base oil that provides exceptional wear protection and deposits and sludge protection. It maintains a proper viscosity level effectively, reducing starting problems. It helps extend engine life and has extended drain interval. The formula is ideal for cars driving in stop-and-go traffic.

Applications

- Suitable for passenger cars and light-duty gasoline and diesel engines without after-treatment systems.

Meets Performance

API SP
ACEA A3/B4
MB 229.3
VW 502 00/505 00
RN 0710/ RN 0700
PSA B71 2296

Features & Benefits

- **Wear Reduction:** Minimizes wear and tear to extend engine life.
- **Deposit Control:** Prevents sludge buildup and keeps engine parts exceptionally clean.
- **Fuel Economy:** Reduces friction for enhanced fuel efficiency and lower emissions.
- **Cold Start Protection:** Ensures effective lubrication and protection immediately after a cold start.
- **Oxidation Stability:** Offers robust resistance to oxidation, ensuring lasting performance.
- **Engine Protection:** Shields against LSPI and provides additional chain wear protection for GDI engines.

Typical Properties

Properties	Test Method	Typical value
Appearance	Visual	Bright & Clear
ASTM Color	ASTM D1500/D6045	2.5
Density @15 °C	ASTM D4052	0.8546
Kinematic Viscosity @40 °C	ASTM D445	87.88
Kinematic Viscosity @100 °C	ASTM D445	14.22
Viscosity Index	ASTM D2270	168
Flash Point, COC	ASTM D92	228
Pour Point	ASTM D5950/D6892	-45
Total Base Number	ASTM D2896	10.7
Cold Cranking Simulator@-30 °C	ASTM D5293	6,385