

NADIR UC500 T

Ultrafiltration Membrane

NADIR UC500 is a regenerated cellulose (RC) ultrafiltration membrane with a nominal molecular weight cut-off (M.W.C.O) of 500,000 Da. This membrane is commonly used in environmental, metal, paint, paper, and pharmaceutical applications. UC500 membrane sheet is available in dry flat sheet rolls and is FDA compliant. systems with a pH range of 0 - 14. NP030 membrane sheet is available in dry flat sheet rolls and is FDA compliant.

MEMBRANE CHARACTERISTICS

Membrane Chemistry	Regenerated Cellulose (RC)
Backing Material	Non-Woven Polyester
Nominal M.W.C.O. (Da)	500,000
Permeability LMH/bar (GFD/psi) ^a	≥ 170 (≥ 6.9)
Thickness (µm)	240 - 280
pH Range	2.0 - 11.0
Temperature Range	5 - 55°C

a) Test conditions: Clean water, 2 bar (29 psi), 20°C (68°F), crossflow operation. Membrane specifications may change without notice as design revisions occur.

IMPORTANT INFORMATION

Standard Sizes: NADIR flat sheet membrane is available in a sample size of 200 mm x 300 mm (7.87 in x 11.81 in) and in a nominal roll size of 150 m x 1016 mm (492 ft x 40.0 in). Custom lengths may be available on request.

Initial Flush: MANN+HUMMEL Water & Membrane Solutions recommends flushing membrane for 30 minutes and discarding permeate during the flush prior to operation.

Storage: Membrane shipped dry should be stored away from direct sunlight in a cool, dry place. Please see Membrane Storage Guide - Flat Sheet Membrane (TSG-O-011).

Contact

Americas

USA: +1 805 964 8003
sales.mnus@microdyn-nadir.com

Asia

APAC: +65 6457 7533
info.wfs@mann-hummel.com
China: +86 10 8413 9860
waterchina@mann-hummel.com

Europe

Germany: +49 611 7118 7480
Italy: +39 0721 1796201
info.wfs@mann-hummel.com

Leadership in Filtration

Rev. 2501

MANN+
HUMMEL