

# NADIR UP010 P

## Ultrafiltration Membrane

NADIR UP010 is a 10,000 Dalton molecular weight cut off (M.W.C.O.) polyethersulfone ultrafiltration membrane that is used in many different applications ranging from food and dairy process applications to industrial water purification. UP010 membrane sheet is available in dry flat sheet rolls and is FDA compliant.

### MEMBRANE CHARACTERISTICS

Membrane Chemistry	Polyethersulfone (PES)
Backing Material	Polypropylene
Nominal M.W.C.O. (Da)	10,000
Permeability LMH/bar (GFD/psi) <sup>a</sup>	≥ 50.0 (≥ 2.0)
Thickness (μm)	210 – 250
pH Range	0.0 – 14.0
Chlorine Tolerance <sup>b</sup>	200 ppm (sanitization) at pH ≥ 10.5

a) Test conditions: Clean water, 4 bar (58 psi), 20°C (68°F), crossflow operation. Membrane specifications may change without notice as design revisions occur.

b) For daily short term cleaning: maximum 50°C (125°F), 30 min.

### IMPORTANT INFORMATION

**Standard Sizes:** NADIR flat sheet membrane is available in a sample size of 200 mm x 300 mm (7.87 in x 11.81 in) and in a nominal roll size of 150 m x 1016 mm (492 ft x 40.0 in). Custom lengths may be available on request.

**Initial Flush:** MANN+HUMMEL Water & Membrane Solutions recommends flushing membrane for 30 minutes and discarding permeate during the flush prior to operation.

**Storage:** Membrane shipped dry should be stored away from direct sunlight in a cool, dry place. Please see Membrane Storage Guide – Flat Sheet Membrane (TSG-O-011).

## Contact

### Americas

USA: +1 805 964 8003  
sales.mnus@microdyn-nadir.com

### Asia

APAC: +65 6457 7533  
info.wfs@mann-hummel.com  
China: +86 10 8413 9860  
waterchina@mann-hummel.com

### Europe

Germany: +49 611 7118 7480  
Italy: +39 0721 1796201  
info.wfs@mann-hummel.com

Leadership in Filtration

Rev. 2501

**MANN+**  
**HUMMEL**