



Material Safety Data Sheet

Date Prepared December 2014

Identification

Product Name: Pergo Laminate flooring

Description: Floor covering elements with surface layers consisting of one or more thin sheets of paper, impregnated with melamine. By the simultaneous action of heat and pressure, these sheets are pressed on a wood-based panel (HDF).

Hazardous Ingredients

#1 Identification: Formaldehyde

Exposure Limits: ACGIH Limit = 1 ppm 8-hr TWA 2 ppm STEL
OSHA Limit = 1 ppm 8-hr TWA 2ppm STEL

Formaldehyde Emmisions: class E1, according to EN 717

#2 Identification: Wood Dust

Exposure Limits: OSHA PEL-TWA 5mg/rn3
OSHA PEL-STEL 10mg/m3

Potential Airborne Releases: Manual or mechanical cutting or abrasion processes performed on the product can result in the generation of wood dust.

Physical Characteristics

Boiling Point:	N/A
Density	$\geq 800\text{kg/m}^3$
Vapor Pressure:	N/A
Melting Point:	N/A
Vapor Density:	N/A
Reactivity in Water:	N/A
Evaporation Rate:	N/A
Appearance:	Varies by Species and decor number

Fire and Explosion Data

Flash Point:	N/A
Fire classification:	class Cfl-s1 according to EN 9239-1

Explosive Limits
In Air: The product listed in this MSDS is not an explosion hazard. Sawing, Sanding, or Machining could result in the by-product wood dust. Wood dust may present a strong to severe explosion hazard if a dust cloud contacts an ignition source.

Fire Extinguishing
Media: Water, Carbon Dioxide, Sand

Special Fire Fighting
Procedures: Fire fighting procedures for wood are well known.

Health Hazard Data

1.1 Formaldehyde Vapor / Signs and Symptoms of exposure:

Acute=May cause temporary irritation of skin, eyes, or respiratory systems. May cause Sensitization in susceptible individuals.

Chronic=Numerous epidemiological studies have failed to demonstrate a relationship between Formaldehyde exposure and nasal cancer or pulmonary diseases such as emphysema or lung Cancer. UAREP concluded that there was no "Convincing Evidence" that formaldehyde exposure causes cancer in humans. Rats exposed to 14ppm of formaldehyde for 24 months in a laboratory developed nasal cancer. Exposure of 6ppm did not result in statistically significant levels. The NCI epidemiology study of 26,000 workers found little evidence linking formaldehyde exposure to cancer. Formaldehyde is classified by OSHA, NTP and IARC as a probable or potential carcinogen.

1.2 Medical conditions aggravated by formaldehyde exposure:

Respiratory conditions or allergies

1.3 Emergency First Aid Procedures:

Inhalation: Remove to fresh air

Eyes: Remove to fresh air

Skin: Remove to fresh air

Ingestion: N/A

If irritation or other symptoms persist, consult a physician.

2.1 Wood Dust

Eye Contact: Wood Dust can cause mechanical irritation

Skin Contact: Various species of wood dust may evoke allergy in sensitive individuals

Ingestion: Not likely to occur

Burning: According to ISO/DIS 5660 tests, the toxicity index of fire effluents was small, but there are many compounds in smoke oases which can cause irritation to eyes, nose & throat.

Inhalation of wood dust: Wood dust may cause nasal dryness, irritation and obstruction.

Coughing, wheezing and sneezing: sinusitis and prolonged colds have also been reported.

Depending on species, wood dust may cause dermatitis on prolonged, repetitive contact; may cause respiratory sensitization and/or irritation. IARC classifies wood dust as a carcinogen to human (Group 1). This classification is based primarily on IARC's evaluation of increased risk in the occurrence of aden carcinomas of the nasal cavities and para nasal sinuses associated with the exposure to wood dust. IARC did not find sufficient evidence to associate cancer of the oropharynx, hypo pharynx, lung, lymphatic and hematopoietic systems, stomach, colon or rectum with exposure to wood dust.

Wood Dust classification from ACGIH: Hard Woods and Softwoods (non-allergenic); "A4 irritation, mucostasis" except Birch and Oak.

2.2 Emergency and First Aid Procedures:

Eye contact: Flush eyes with large amounts of water. Enable fresh air environment. If irritation persists, get medical attention.

Skin contact: Wash affected areas with soap and water. Get medical advice if rash or persistent irritation or dermatitis occurs.

Inhalation: Remove to fresh air. Get medical advice if persistent irritation, severe coughing or breathing difficulty occurs.

Ingestion: Not applicable

Reactivity Data

Conditions contributing to Instability:

Stable under normal conditions

Incompatibility: Avoid contact with oxidizing agents & strong acids. Avoid open flame

Hazardous decomposition products:

Thermal and/or thermal-oxidative decomposition can produce irritating and toxic fumes and Gases, including carbon monoxide, aldehydes and organic acids.

Hazardous polymerization: N/A

Precautions, Safe Handling

Personal Protective equipment:

Wear goggles or safety glasses when manufacturing or machining the product.

Wear NIOSH/MSHA approved respirator when allowable exposure limits may be exceeded.

Other protective equipment such as gloves and outer garments may be needed depending on dust conditions.

Waste Disposal Method:

Incinerate or landfill in accordance with local, state and federal regulations.

Important-Disclaimer

The information and data herein are believed to be accurate and have been compiled from sources believed to be reliable. Unilin Flooring Bvba. make no warranty of any kind, expressed or implied, concerning the accuracy or completeness of the information and data herein. Unilin Flooring Bvba will not be liable for claims relating to any party's use of or reliance on information and data contained herein regardless of whether it is claimed that the information and data are inaccurate, incomplete or otherwise misleading. It is offered for your consideration, investigation and verification. Due to possible technical changes it is incumbent upon the user to obtain the most up to date information.