

N 90
D95DAP8NOB
WORKTOP VENTILATION
BLACK
90 CM WIDE



COOKING PASSION SINCE 1877

The quiet Downdraft hood with a high extraction rate can be extended from the worktop whenever steam and culinary odours arise.

- ✓ Extendable – Emerges only when needed and sits neatly behind the hob for a clear view in the kitchen
- ✓ Quiet operation – Particularly quiet due to its noise-optimised design
- ✓ Space-saving miracle – Fits neatly behind the hob for more use of the cabinet space underneath
- ✓ Integrated lighting – Our downdraft hood with integrated LED lights for clear lighting over your hob
- ✓ Flexible installation – A range of installation options make the most of your cabinet space

Features

Technical Data

Approval certificates : CE
Length of electrical supply cord (cm) : 150
Required niche size for installation (HxWxD) : 735mm x 844mm x 104mm
Net weight (kg) : 44.0
Type of control : Electronic
Number of speed settings : 3-stage + 2 intensive
Maximum output air extraction (m³/h) : 530
Boost position output recirculating (m³/h) : 510
Maximum output recirculating air (m³/h) : 460
Boost position air extraction (m³/h) : 750
Number of lights (Stck) : 1
Noise level (dB(A) re 1 pW) : 62
Diameter of air outlet (mm) : 150
Grease filter material : Washable aluminium
EAN code : 4242004230731
Connection rating (W) : 317
Current (A) : 10
Voltage (V) : 220-240
Frequency (Hz) : 50
Plug type : GB plug
Installation type : Built-in



4 242004 230731

N 90
D95DAP8NOB
WORKTOP VENTILATION
BLACK
90 CM WIDE

Features

Key performance features:

- Energy Efficiency Class: A (at a range of energy efficiency classes from A++ to E)*
- Extraction rate according to EN 61591 ø 15 cm:
max. Normal use 530 m³/h
Intensive 750 m³/h
- Noise max. Normal Level: 62 dB*

Features

- Electronic controls
- 3 power levels and 2 intensive settings
- Touch control
- 1 x 7W LED-module
- Colour Temperature: 3500 K
- Automatic after running (10 minutes)
- 2 metal grease filter cassettes
- Saturation indicator for metal and charcoal filter
- Rim ventilation

Design

- Black
- Worktop ventilation
- For installation in a kitchen cabinet
- Extension height 300 mm

Performance/technical information

- Suitable for ducted extraction and recirculation
- For recirculated extraction recirculating kit (accessory) needed
- In recirculation mode no combination with gas hobs allowed.
- Extraction rate according to EN 61591 ø 15 cm:
max. Normal use 530 m³/h
Intensive 750 m³/h
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air:
Max. normal use: 62 dB(A) re 1 pW (48 dB(A) re 20 µPa sound pressure)
Intensive: 67 dB(A) re 1 pW (53 dB(A) re 20 µPa sound pressure)
- Noise max. Normal Level: 62 dB*
- Power rating: 317 W
- Light Intensity: 203 lux
- Colour Temperature: 3500 K
- Electrical cable length 1.5 m
- Diameter pipe Ø 150 mm (Ø 150 mm enclosed)
- Dimensions exhaust air (HxWxD): 735-1035 x 918 x 268 mm
- Dimensions recirculating (HxWxD): 735-1035 x 918 x 268 mm
- Energy Efficiency Class: A (at a range of energy efficiency classes from A++ to E)*
- Blower Efficiency Class: A*
- Lighting Efficiency Class: A*
- Grease Filtering Efficiency Class: D*
- Average Energy Consumption: 53.5 kWh/year*

Optional accessories

- Recirculating kit

* In accordance with the EU-Regulation No 65/2014

N 90
D95DAP8NOB
WORKTOP VENTILATION
BLACK
90 CM WIDE

Dimensioned drawings

N 90
D95DAP8NOB
WORKTOP VENTILATION
BLACK
90 CM WIDE

Dimensioned drawings