



# SAFETY DATA SHEET – Gorilla Glue

Date Revised: 20/1/2017

Version 1.2

## FOR CHEMICAL EMERGENCY:

During Business Hours: (800) 966-3458 | Outside Business Hours: (800) 420-7186

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 2015/830

## 1. SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

### 1.1 Product identifier

Product Name	Gorilla Glue.
Synonym(s)	Polyurethane Adhesive.
CAS No.	Mixture.
EINECS No.	Mixture.

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified use(s)	Consumer Adhesives for building, carpentry, or hobby projects.
Uses advised against	None known.

### 1.3 Details of the supplier of the Safety Data Sheet

Company Identification	Gorilla Glue Europe Ltd. Chorley Business & Technology Centre East Terrace Euxton Lane Chorley PR7 6TE, United Kingdom.
Telephone	01257 241319
Fax	01257 273820
E-mail	eusales@gorillaglue.com

### 1.4 Emergency telephone number

National Poisons Information Service	111
Emergency Phone No.	+44 (0) 1257 241319 (During Business Hours) +1 651-603-3429 (Outside Business Hours)

## 2. SECTION 2: HAZARDS IDENTIFICATION

### 2.1 Classification of the substance or mixture

<b>Regulation (EC) No. 1272/2008 (CLP)</b>	Skin Irrit. 2; Causes skin irritation. Eye Irrit. 2; Causes serious eye irritation. Skin Sens. 1; May cause an allergic skin reaction. Resp. Sens. 1; May cause allergy or asthma symptoms or breathing difficulties if inhaled. Acute Tox. 4; Harmful if inhaled. Carc. 2; Suspected of causing cancer. STOT SE 3; May cause respiratory irritation. STOT RE 2; May cause damage to organs through prolonged or repeated exposure.
--	--

### 2.2 Label elements

Product Name	According to Regulation (EC) No. 1272/2008 (CLP) Gorilla Glue.
--------------	---



# SAFETY DATA SHEET – Gorilla Glue

Date Revised: 20/1/2017

Version 1.2

## FOR CHEMICAL EMERGENCY:

During Business Hours: (800) 966-3458 | Outside Business Hours: (800) 420-7186

Hazard pictogram(s)



GHS07

GHS08

Signal word(s)

Danger.

Hazardous Ingredient(s)

Aromatic polyisocyanate, Isocyanic acid, polymethylene polyphenylene ester, 4,4'-Methylenediphenyl diisocyanate, Benzene, 1,1'-methylenebis(isocyanato-

Hazard statement(s)

H315: Causes skin irritation.  
H317: May cause an allergic skin reaction.  
H319: Causes serious eye irritation.  
H332: Harmful if inhaled.  
H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
H335: May cause respiratory irritation.  
H351: Suspected of causing cancer.  
H373: May cause damage to organs through prolonged or repeated exposure.  
EUH204: Contains isocyanates. May produce an allergic reaction.

Precautionary statement(s)

P102: Keep out of reach of children.  
P260: Do not breathe mist/vapours/spray.  
P280: Wear protective gloves/protective clothing/eye protection/ respiratory protection.  
P302+P352: IF ON SKIN: Wash with plenty of water.  
P304 + P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P501: Dispose of contents/container in accordance with local, regional, national, and international regulations.

## 2.3 Other hazards

None.

## 2.4 Additional Information

For full text of H/P statements see section 16.



# SAFETY DATA SHEET – Gorilla Glue

Date Revised: 20/1/2017

Version 1.2

## FOR CHEMICAL EMERGENCY:

During Business Hours: (800) 966-3458 | Outside Business Hours: (800) 420-7186

### 3. SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

#### 3.1 Substances

Not applicable.

#### 3.2 Mixtures

EC Classification No. 1272/2008

Hazardous ingredient(s)	%W/W	CAS No.	EC No.	EC INDEX No.	Classification
Isocyanic acid, polymethylene polyphenylene ester polymer with 1,2-ethanediamine, methyloxirane and 1,2-propanediol	40-70	67815-87-6	None assigned	None assigned	Skin Sens. 1; H317, Resp. Sens. 1; H334
4,4'-Methylenediphenyl diisocyanate	10-30	101-68-8	202-966-0	615-005-00-9	Acute Tox. 4; H332, Skin Irrit. 2; H315, Eye Irrit. 2; H319, Skin Sens. 1; H317, STOT SE 3; H335, Resp. Sens. 1; H334, Carc. 2; H351, STOT RE 2; H373 Specific Concentration Limits (C >= 0,1) Resp. Sens. 1; H334, (C >= 5) Eye Irrit. 2; H319, (C >= 5) Skin Irrit. 2; H315, (C >= 5) STOT SE 3; H335
Isocyanic acid, polymethylene polyphenylene ester	10-30	9016-87-9	618-498-9	None assigned	Acute Tox. 2; H330, Skin Irrit. 2; H315, Eye Irrit. 2; H319, STOT SE 3; H335, Resp. Sens. 1; H334, STOT RE 2; H373
Benzene, 1,1'-methylenebis[isocyanato-	1-5	26447-40-5	247-714-0	615-005-00-9	Acute Tox. 2; H330, Skin Irrit. 2; H315, Eye Irrit. 2; H319, Skin Sens. 1; H317, STOT SE 3; H335, Resp. Sens. 1; H334, Carc. 2; H351, STOT RE 2; H373 Specific Concentration Limits (C >= 0,1) Resp. Sens. 1; H334, (C >= 5) Eye Irrit. 2; H319, (C >= 5) Skin Irrit. 2; H315, (C >= 5) STOT SE 3; H335



# SAFETY DATA SHEET – Gorilla Glue

Date Revised: 20/1/2017

Version 1.2

## FOR CHEMICAL EMERGENCY:

During Business Hours: (800) 966-3458 | Outside Business Hours: (800) 420-7186

### 3.3 Additional Information

For full text of H/P statements see section 16.

## 4. SECTION 4: FIRST AID MEASURES



### 4.1 Description of first aid measures

General information

Do not give anything by mouth to an unconscious person. Get medical advice/attention if you feel unwell. (show the label if possible).

Inhalation

Using proper respiratory protection, immediately move the exposed person to fresh air. Get medical attention immediately.

Skin Contact

Remove contaminated clothing. Gently wash with plenty of soap and water. Continue to wash the affected area for at least 15 minutes. Call a POISON CENTER/doctor if you feel unwell. Wash contaminated clothing before reuse.

Eye Contact

Flush eyes with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician.

Ingestion

Rinse mouth. Do not induce vomiting. Immediately call a POISON CENTER or doctor/physician.

### 4.2 Most important symptoms and effects, both acute and delayed

Skin Contact: Causes skin irritation. May produce an allergic reaction.

Eye Contact: Causes serious eye irritation.

Inhalation: Harmful if inhaled. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause respiratory irritation.

Ingestion: Likely to be harmful or have adverse effects.

Chronic Symptoms: May cause damage to organs through prolonged or repeated exposure. Suspected of causing cancer.

### 4.3 Indication of any immediate medical attention and special treatment needed

If medical advice is needed, have product container or label at hand.

## 5. SECTION 5: FIREFIGHTING MEASURES

### 5.1 Extinguishing Media

Suitable Extinguishing Media

Small fire: Foam, CO<sub>2</sub> or dry powder.

Large fire: Alcohol-resistant foams.

If water is used, it should be used in very large quantities and from a safe distance.



# SAFETY DATA SHEET – Gorilla Glue

Date Revised: 20/1/2017

Version 1.2

## FOR CHEMICAL EMERGENCY:

During Business Hours: (800) 966-3458 | Outside Business Hours: (800) 420-7186

Unsuitable Extinguishing Media

### 5.2 Special hazards arising from the substance or mixture

Do not use a heavy water stream. Use of heavy stream of water may spread fire.

Non-flammable. Non-explosive.

The reaction between water and isocyanate may be vigorous.

Exothermic reaction with amines and alcohols; reacts with water forming heat, CO<sub>2</sub>, and insoluble polyurea. The combined effects of CO<sub>2</sub> and heat can produce enough pressure to rupture a closed container.

### 5.3 Advice for firefighters

Exercise caution when fighting any chemical fire. Do not allow runoff to enter drains, sewers or watercourses. Evacuate area. Do not reseal contaminated containers; a chemical reaction generating CO<sub>2</sub> gas pressure may occur resulting in rupture of the container. Dense smoke is emitted when product is burned without sufficient oxygen. When using water spray, boil-over may occur when product temperature reaches the boiling point of water, and the reaction forming CO<sub>2</sub> will accelerate. Fire fighters should wear proper protective clothing including respiratory protection.

## 6. SECTION 6: ACCIDENTAL RELEASE MEASURES

### 6.1 Personal precautions, protective equipment and emergency procedures

Avoid contact with skin, eyes or clothing. Avoid breathing vapours. Ensure adequate ventilation. Evacuate if necessary. Stop leak if safe to do so. Ensure suitable personal protection during removal of spillages.

### 6.2 Environmental precautions

Avoid run off to waterways and sewers.

### 6.3 Methods and material for containment and cleaning up

Clean up spill immediately. Cover spills with inert absorbent material. Remove mechanically but cautiously as this process can generate heat. Absorb remaining liquid in sand or inert absorbent and remove to safe place. After 15 minutes, transfer to waste container and do not seal (evolution of CO<sub>2</sub>). Keep damp in a safe ventilated area for several days. Dispose of empty containers and wastes safely.

### 6.4 Reference to other sections

See Also Section: 8, 13

## 7. SECTION 7: HANDLING AND STORAGE

### 7.1 Precautions for safe handling

General hygiene measures for the handling of chemicals are applicable. Wash (hands and exposed skin) thoroughly after handling. Do not eat, drink or smoke when using this product.



## SAFETY DATA SHEET – Gorilla Glue

Date Revised: 20/1/2017

Version 1.2

### FOR CHEMICAL EMERGENCY:

During Business Hours: (800) 966-3458 | Outside Business Hours: (800) 420-7186

#### 7.2 Conditions for safe storage, including any incompatibilities

Storage Temperature  
Storage Life  
Incompatible materials

Store in a cool/low-temperature, well-ventilated (dry) place. Keep away from: heat and alcohols, amines or other materials that react with isocyanates. Keep out of reach of children and animals. Keep container closed when not in use. Store locked up.

Ambient.

Stable under normal conditions.

Acids, Alkalis, Strong oxidising agents, Amines, Alcohols.

#### 7.3 Specific end use(s)

Consumer Adhesives for building, carpentry, or hobby projects.

## 8. SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1 Control parameters

#### 8.1.1 Occupational Exposure Limits

SUBSTANCE	CAS No.	LTEL (8 hr TWA ppm)	LTEL (8 hr TWA mg/m <sup>3</sup> )	STEL (ppm)	STEL (mg/m <sup>3</sup> )	Note
Isocyanic acid, polymethylene polyphenylene ester polymer with 1,2-ethanediamine, methyloxirane and 1,2-propanediol	67815-87-6					None assigned
4,4'-Methylenediphenyl diisocyanate	101-68-8					None assigned
Isocyanic acid, polymethylene polyphenylene ester	9016-87-9					None assigned
Benzene, 1,1'-methylenebis[isocyanato -	26447-40-5					None assigned

#### 8.1.2 Biological limit value

Not established.

#### 8.1.3 PNECs and DNELs

Not established.

### 8.2 Exposure controls

#### 8.2.1 Appropriate engineering controls

Provide adequate ventilation to ensure that the occupational exposure limit is not exceeded. Guarantee that the eye flushing systems and safety showers are located close to the working place.

#### 8.2.2 Personal protection equipment

Eye/face protection

Wear protective eyewear (goggles, face shield, or safety glasses).





# SAFETY DATA SHEET – Gorilla Glue

Date Revised: 20/1/2017

Version 1.2

## FOR CHEMICAL EMERGENCY:

During Business Hours: (800) 966-3458 | Outside Business Hours: (800) 420-7186



Skin protection (Hand protection/ Other)



Respiratory protection



Thermal hazards

Wear protective clothing and gloves: Chemically resistant materials and fabrics.

Wear suitable respiratory protective equipment if exposure to levels above the occupational exposure limit is likely.

Not applicable.

### 8.2.3 Environmental Exposure Controls

Avoid run off to waterways and sewers.

## 9. SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1 Information on basic physical and chemical properties

Appearance	Liquid.
Colour	Brown.
Odour	Earthy, Musty.
Odour Threshold	No data.
pH	Not applicable.
Melting Point/Freezing Point	No data.
Initial boiling point and boiling range	208°C (406,40°F)
Flash Point	> 93°C (199,4°F) [Closed cup]
Evaporation rate	No data.
Flammability (solid, gas)	No data.
Upper/lower flammability or explosive limits	Not applicable.
Vapour pressure	< 0,0001 mm Hg @ 25°C (Isocyanates)
Vapour density	No data.
Relative density	1,14 (Water = 1)
Density (g/cm <sup>3</sup> )	1,14 @ 20°C
Solubility(ies)	Insoluble in water.
Partition coefficient: n-octanol/water	No data.
Auto-ignition temperature	No data.
Decomposition Temperature	No data.
Viscosity	4000 – 7000 mPa•s @ 25°C
Explosive properties	No data.
Oxidising properties	No data.

### 9.2 Other information

None.

## 10. SECTION 10: STABILITY AND REACTIVITY

### 10.1 Reactivity

Exothermic reaction with amines and alcohols; reacts with water forming heat, CO<sub>2</sub>, and insoluble polyurea.

### 10.2 Chemical stability

Stable under normal conditions.

### 10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.



## SAFETY DATA SHEET – Gorilla Glue

Date Revised: 20/1/2017

Version 1.2

### FOR CHEMICAL EMERGENCY:

During Business Hours: (800) 966-3458 | Outside Business Hours: (800) 420-7186

#### 10.4 Conditions to avoid

No hazardous reactions known if used for its intended purpose.

#### 10.5 Incompatible materials

Keep away from heat, sources of ignition and direct sunlight. Protect from freezing.

#### 10.6 Hazardous Decomposition Product(s)

Acids, Alkalis, Strong oxidising agents, Amines, Alcohols.

Oxides of carbon, MDI vapour, Nitrogen compounds, Cyanides, Isocyanates.

## 11. SECTION 11: TOXICOLOGICAL INFORMATION

### 11.1 Information on toxicological effects

#### Acute toxicity

Harmful if inhaled.

#### Oral

ATE (CLP) (4 hour(s)) = 1500 mg/l

#### Dermal

Benzene, 1,1'-methylenebis[isocyanato-:

LD50 (rat) = > 7400 mg/kg

#### Inhalation

Benzene, 1,1'-methylenebis[isocyanato-:

LD50 (rabbit) = > 6200 mg/kg

Isocyanic acid, polymethylene polyphenylene ester:

LC50 (rat) (4 hour(s)) = 490 mg/m<sup>3</sup>

Benzene, 1,1'-methylenebis[isocyanato-:

LC50 (rat) (4 hour(s)) = 0.369 mg/L

#### Inhalation Note

Original Gorilla Glue is composed of both 4,4'-Methylenediphenyl diisocyanate (MDI) and Isocyanic acid, polymethylene polyphenylene ester (PMDI). However, product data has demonstrated that, during consumer use, airborne concentrations of MDI/PMDI were nondetectable. Based on this data, Original Gorilla Glue does not warrant an acute inhalation hazard classification.

#### Skin corrosion/irritation

Causes skin irritation.

#### Serious eye damage/irritation

Causes serious eye irritation.

#### Respiratory or skin sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.

#### Germ cell mutagenicity

Not classified.

#### Carcinogenicity

Suspected of causing cancer.

#### Reproductive toxicity

Not classified.

#### STOT - single exposure

May cause respiratory irritation.

#### STOT - repeated exposure

May cause damage to organs through prolonged or repeated exposure.

#### Aspiration hazard

Not classified.

### 11.2 Other information

None.

## 12. SECTION 12: ECOLOGICAL INFORMATION

### 12.1 Toxicity

Low toxicity to aquatic organisms.





# SAFETY DATA SHEET – Gorilla Glue

Date Revised: 20/1/2017

Version 1.2

## FOR CHEMICAL EMERGENCY:

During Business Hours: (800) 966-3458 | Outside Business Hours: (800) 420-7186

12.2 Persistence and degradability

12.3 Bioaccumulative potential

12.4 Mobility in soil

12.5 Results of PBT and vPvB assessment

12.6 Other adverse effects

Benzene, 1,1'-methylenebis[isocyanato-:

NOEC(Acute)(14 days) =  $\geq 1000$  mg/kg.

Biodegradation (0% @ 28 days).

The product has no potential for bioaccumulation.

Benzene, 1,1'-methylenebis[isocyanato-:

Bioconcentration factor (BCF)(Fish) = 3 – 14.

Insoluble in water. The product is predicted to have low mobility in soil.

No information available.

Avoid release to the environment.

## 13. SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Dispose of wastes in an approved waste disposal facility.

13.2 Additional Information

Disposal should be in accordance with local, state or national legislation.

## 14. SECTION 14: TRANSPORT INFORMATION

Not classified as dangerous for transport.

14.1 UN number

Not applicable.

14.2 UN Proper Shipping Name

Not applicable.

14.3 Transport hazard class(es)

Not applicable.

14.4 Packing Group

Not applicable.

14.5 Environmental hazards

Not applicable.

14.6 Special precautions for user

Not applicable.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable.

## 15. SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1 EU regulations

Authorisations and/or restrictions on use  
Candidate List of Substances of Very High Concern for Authorisation

All chemicals are not listed.

REACH: ANNEX XIV list of substances subject to authorisation

All chemicals are not listed.

REACH: Annex XVII Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Gorilla Glue

3. Liquid substances or mixtures which are regarded as dangerous in accordance with Directive 1999/45/EC or are fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No. 1272/2008.

4,4'-Methylenediphenyl diisocyanate (CAS No.: 101-68-8)

56. Methylenediphenyl diisocyanate (MDI)



# SAFETY DATA SHEET – Gorilla Glue

Date Revised: 20/1/2017

Version 1.2

## FOR CHEMICAL EMERGENCY:

During Business Hours: (800) 966-3458 | Outside Business Hours: (800) 420-7186

Community Rolling Action Plan (CoRAP)

### 15.1.2 National regulations

### 15.2 Chemical Safety Assessment

56.a. Methylenediphenyl diisocyanate (MDI)  
isomers: 4,4'-Methylenediphenyl diisocyanate

All chemicals are not listed.

None known.

Not applicable.

## 16. SECTION 16: OTHER INFORMATION

The following sections contain revisions or new statements: 11

### LEGEND

LTEL	Long Term Exposure Limit
STEL	Short Term Exposure Limit
DNEL	Derived No Effect Level
PNEC	Predicted No Effect Concentration
PBT	Persistent, Bioaccumulative and Toxic
vPvB	very Persistent and very Bioaccumulative
Eye Irrit. 2	Serious eye damage/irritation Category 2
Skin Irrit. 2	Skin corrosion/irritation Category 2
Acute Tox. 2	Acute toxicity Category 2
Acute Tox. 4	Acute toxicity Category 4
Skin Sens. 1	Respiratory/skin sensitisation Category 1
Resp. Sens. 1	Respiratory/skin sensitisation Category 1
Carc. 2	Carcinogenicity Category 2
STOT SE 3	Specific target organ toxicity — single exposure Category 3
STOT RE 2	Specific target organ toxicity — repeated exposure Category 2

### Hazard statement(s)

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H373	May cause damage to organs through prolonged or repeated exposure.

### Disclaimers

The information presented in this Safety Data Sheet was prepared by qualified personnel and to the best of our knowledge is true and accurate. The information and recommendations are furnished for this product with the understanding that the purchaser will independently determine the suitability of the product for this purpose. This data does not constitute a warranty, expressed or implied, statutory or otherwise, nor is it representation for which The Gorilla Glue Company assumes legal responsibility. The data is submitted for the user's information and consideration only. Any use of this product must be determined by the user to be in accordance with applicable federal, state, provincial and local laws and regulations.

### Annex to the extended Safety Data Sheet (eSDS)

Not applicable.



## SAFETY DATA SHEET – Gorilla Glue

Date Revised: 20/1/2017

Version 1.2

### FOR CHEMICAL EMERGENCY:

During Business Hours: (800) 966-3458 | Outside Business Hours: (800) 420-7186