94128
TRONO STICK



General Information

Material number	94128
Type	wall light
Product segment	Outdoor

Dimensions

Article Height (in mm)	410
Article Length (in mm)	105
Net Weight	1.45 Kilogram
Article Overhang (in mm)	175

Material & Colour

Enclosure Material	stainless steel
Enclosure Colour	stainless steel
Glass/Shade Material	glass, plastic
Glass/Shade Colour	clear

94128
TRONO STICK

Functionality

Switch Type	sensor
Sensor Angle (in °)	110
Burning Time min. (in sec.)	15
Burning Time max. (in sec.)	420
Distance (in Meter)	5
Function	corner mounting possible LED not replaceable
Battery	No

Technical Information

Protection Degree	IP44
Protection Class	1
Mains Voltage	220-230V,50/60Hz
Operation Voltage	220-230V,50/60Hz
Dimmable	No
max. Wattage (1)	1X3W
max. Wattage (2)	1X3,7W

Illuminant 2

Socket Type (2)	LED
Illuminant Type (2)	LED-MODUL
Illuminant incl. (2)	Inclusive
Energy Efficiency Class	incl.LED + incl.LM
Dimmable	No
Function	corner mounting possible LED not replaceable

Illuminant 1

Socket Type (1)	GU10
Illuminant Type (1)	GU10-LED
Illuminant incl. (1)	Inclusive
Beamangle (in °)	110
Nominal Luminous Flux (in lm)	240
Equivalence With Incandescent Lamp (W)	23
Colour Temperature	3000K warm white
Nominal Lifetime (in h)	15000
Switching Cycles	15000
Colour Rendering Index (Ra, CRI)	>80
Energy Efficiency Class	A+
kW/1000h	3
Dimmable	No
Rated Lamp Power (0,1W precision)	3.1000
Colour Tolerance (LED, SDCM)	<6

94128
TRONO STICK



GU10 | 1X3W | 1X x 240lm | 1X3.7 W | 1X x 280lm | IP44

Contact | Support
eglo.com/uk/eglo-worldwide